



Superior Pavement Marking Products

WHEN YOU WANT IT. WHERE YOU WANT IT.

www.crownusa.com

CROWN USA, INC. NOT ONLY OFFERS SUPERIOR PRODUCTS SUCH AS **TUFFLINE® KWIKLINE® AND ECOTHERM® KWIKLINE®** “HOT-APPLIED” THERMOPLASTIC PAVEMENT MARKINGS, WE OFFER A SUPERIOR CUSTOMER SERVICE EXPERIENCE. CROWN’S FULL SERVICE TEAM CAN AID YOU WITH:



Selecting proper product based on specification, location, performance, and/or application equipment being used



Arranging shipments around the World



Working with Federal, State, or Local specifying bodies on your behalf to ensure project success



Providing technical product support to ensure proper application and long-term project success



Answering specific questions related to your project to ensure specification and performance guidelines are met

Get in Touch



PHONE (706) 553 9500
TOLL FREE (800) 457 6267
FAX (706) 553 3958

CALL US TODAY TO LEARN MORE ABOUT OUR PRODUCTS AND HOW CROWN CAN ASSIST YOU WITH YOUR NEXT PROJECT!



TUFFLINE® KWIKLINE® (WHITE) & ECOTHERM® KWIKLINE® (YELLOW)

Crown manufactures a full array of pavement marking products including traditional “Hot-Applied” thermoplastic pavement marking material. **TuffLine® KwikLine® white and EcoTherm® KwikLine® yellow** are offered in both alkyd and hydrocarbon variations. Crown provides custom tailoring of our products to meet customer needs based on specific application setups while also meeting Federal, State, City/County, and/or Country material and performance based specifications. Crown’s products are engineered and manufactured using the latest technology available while also being subjected to vigorous internal Quality Control standards.

COMMON PROPERTIES & BENEFITS

- ◆ Excellent cost-effective choice to paint on low ADT roadways
- ◆ Excellent color retention and durability
- ◆ Provides economical solution to refurbish worn thermoplastic markings
- ◆ Yellow formulated using environmentally friendly lead-free pigment
- ◆ Granular material packaged in meltable 50-lb bags
- ◆ Formulated to be applied using spray setups
- ◆ Designed for applications thicknesses of 30-45mils
- ◆ Applied at temperatures of 350 - 400°F
- ◆ Available in many State/City/County specifications
- ◆ Some of the many Certifications offered with notable adjustments for the products designed performance:
 - AASHTO M 249
 - EPA 3052, 6010B, or 6010 C
 - ASTM D 6628
 - BS 3262
 - AASHTO T 250
 - ASTM D36
 - ASTM E 313
 - Independent Lab Certification



**CROWN
USA INC**

www.crownthermo.com